



4 CHANNEL WALL MOUNT CONTROLLER

LEADERS IN GAS DETECTION

Since 1977

Beacon 410 Model



Features:

- Simultaneously monitors up to 4 channels
- Digital display of all 4 channels
- LEL / O₂ / CO₂ / toxic direct connect sensors
- Accepts any 4-20 mA transmitter, 2 or 3 wire
- 3 programmable alarm levels per channel
- Up to 3 configurable alarm relays per channel
- Zero follower automatically compensates sensor drift
- 4-20 mA analogue & Modbus digital output standard
- 240 VAC or 24 VDC operation
- Audible alarm with silence feature
- Alarm reset switch
- Built in trouble alarm with relay
- Weather proof NEMA 4X enclosure
- Optional strobe & battery backup available

Industry Applications:

- Petrochemical plants
- Refineries
- Water & wastewater treatment plants
- Gas, telephone, & electric utilities
- Parking garages
- Manufacturing facilities
- HVAC
- Laboratories

The Beacon 410 is a highly configurable, microprocessor-based, flexible and easy to use 4 channel gas monitor. It simultaneously displays the gas type, readings, and status for 4 channels of gas detection. The Beacon 410 can monitor any combination of direct connect sensors (LEL combustibles, Oxygen, Hydrogen Sulphide, Carbon Monoxide, Carbon Dioxide and Toxic gas sensors) as well as any 4-20mA transmitters.

Each channel has 3 fully configurable alarm points. A built-in silenceable audible alarm alerts you to alarm conditions. Each channel also has 2 dedicated fully configurable relays and there is also a bank of common relays. The common relays can optionally be configured as additional channel relays allowing up to 3 alarm relays per channel.

Each channel provides a 4-20mA output signal. A digital Modbus interface for remote logging of data via a Modbus network is standard. A Min-Max feature retains high & low peak readings for review at any time. Field calibration is made simple by the easy to use Calibration Mode. A fully configurable high visibility strobe is available as an option. The unit can be powered from 240 VAC, an external 24 VDC source, or a 24 VDC backup battery. A trickle charging battery backup feature is also available as an option.

All features and functions of the Beacon 410 are controlled by easy to use menus on the backlit LCD display. The form-C (SPDT) relay contacts are rated at 10A, 250V, reducing or eliminating the need for additional slave relays. All features of the Beacon 410 are built into the unit so you never need to purchase or maintain any "add-on" cards or components.



OIL & GAS CONFINED SPACE HVAC MINING LABORATORIES COUNCILS DEFENCE SHIPPING FUMIGATION

Control Equipment Pty Ltd ABN 23 009 838 582

Head Office:

Unit 1 / 3 Deakin St
Brendale Qld 4500
Phone: (07) 3481 9000

Postal Address:

PO Box 5904
Brendale Qld 4500
sales@controlequipment.com.au
www.controlequipment.com.au

Offices/Agents in:

Sydney Hobart
Melbourne Auckland
Adelaide Wellington
Perth Christchurch

Physical	
Dimensions:	Height 216mm Width 178 mm Depth: 109 mm
Enclosure:	NEMA 4X non-metallic for indoor and outdoor locations
Conduit Connection:	20mm NPT conduit hubs, 4 provided, for sensor, power and relay wiring.
Wiring Termination:	Screw type terminal block, 14 gauge max.
Power:	240 VAC, or 24 VDC nominal optional– 115 VAC. Battery backup option available.
Controls:	Display PCB Control switches: <ul style="list-style-type: none"> • UP/YES push button switch • ESCAPE push button switch • External reset switch • DOWN/NO push button switch • ENTER push button switch • On/Off toggle switch
Environmental	
Operating Temp:	-20°C to 50°C
Storage Temp:	-20°C to 70°C
Relative Humidity:	0 – 95% RH (non-condensing)
Enclosure Rating:	NEMA-4X enclosure, waterproof, chemical and weather resistant.
Inputs	
Direct Wired Sensors:	LEL, Oxygen, Carbon Monoxide, Hydrogen Sulphide, and Carbon Dioxide. Remote amp not required for less than 15 metres
4-20 mA Sensors:	Accepts any 4-20 mA transmitters (24 VDC, 2 or 3 wire). A wide variety of RKI/Riken sensors are available with 4-20 mA signals. Wiring distances up to 5,000 metres.
Sampling methods:	Diffusion and sample draw heads available.
Outputs	
Relays:	Two flexible, programmable Form-C (C, NO, NC) relays per channel, plus five common relays (Fail, Alarm-1, Alarm-2, Alarm-3, Alarm-Any). Common relays may optionally be assigned to function as additional channel alarm relays, providing for up to three alarm relays per channel. 10A contact rating.
4-20 mA:	Signal output, 4-20 mA (maximum load impedance 500 ohms), per channel
RS-485:	Modbus format RS-485 serial output of all channel data, including gas reading and alarm status.
Display:	4 x 20 backlit LCD display
Audible:	Built-in audible alarm, 94 dB, mounted on enclosure. Coded output: Pulsing = gas alarm, Steady = fail
Visual:	1. Alarm LED's (on Display PCB) <ul style="list-style-type: none"> • Alarm 1, yellow • Alarm 2, orange • Alarm 3, red • Fail, yellow 2. Green pilot LED to indicate AC power connected (on Display PCB) 3. An optional 24 VDC NEMA 4X strobe mounted to top of case
Warranty:	Two year materials and workmanship.

