



Features:

- Stand-alone station (no PC Required)
- Calibration
- Bump Test
- Save Bump Test and Calibration records
- Bump test and calibration records copy to USB
- Includes PC software for viewing/archiving bump test and calibration records

Multi Module System

- Multiple modules connected to a PC (10 max)
- Calibration
- Bump Test
- Automatic calibration/bump test option
- Configure 03 Series parameters
- Archive Bump Test and Calibration records
- Archive data to network location
- Software controlled data retrieval
- Windows 7 compatible

Stand Alone Station

The SDM-03 is a versatile maintenance tool that automates the testing service of a 03 Series portable gas monitor. This docking station can be used as a stand alone device for charging, calibration and bump testing, with all records stored automatically for future upload to a PC via USB flash drive (PC software and flash drive included).

Multi Module System

Automate how you manage and service 03 Series instruments by connecting the SDM-03 to a computer with a USB cable. With the SDM Docking Station controller software, you can simultaneously calibrate, bump test, or archive data for up to ten instruments. Also, download the data logging history from each instrument into one easy to manage locator. SDM-03 stations can be manifolded together to reduce the number of demand flow regulator gas cylinders required.

Head Office:

Unit 1 / 3 Deakin Street
(PO Box 5904)
Brendale QLD 4500 Australia
Ph: +61 (0) 7 3481 9000

Perth Office:

Unit 5 / 30 Enterprise Crescent
Malaga WA 6090 Australia
Ph: +61 (0) 8 6184 7840
sales@controlequipment.com.au

Representatives/Offices in:

Sydney	Melbourne
Hobart	Adelaide
Auckland	Wellington
www.controlequipment.com.au	

ORDERING INFORMATION

Docking Station

81-SDM03-01	Single point calibration station for 03 Series, model SDM-03 with AC Adaptor, flash drive, USB cable, tubing & installation CD
81-SDM03-02	Single point calibration station for 03 Series, model SDM-03 with AC Adaptor, flash drive, USB cable, tubing installation CD & demand flow regulator 34AL/58AL/103L

Highlighted features indicate differences between the various versions of the docking stations.

CALIBRATION EQUIPMENT & ACCESSORIES

81-0078RK-03	Cylinder, 100% N ₂ , 103L
81-0064RK-03	Cylinder, CO 50 ppm in air, 103L
81-0064RK-01	Cylinder, CO 50 ppm in air, 34L
81-0012RK-03	Cylinder, / Methane 50% LEL / in air, 103L
81-0151RK-02	Cylinder, H ₂ S 25 ppm in N ₂ , 58AL
81-1054RK	Regulator, demand flow for 34AL/58AL/103L
81-1055RK	Regulator, demand flow for 17L/34L steel cylinders
82-6050RK	USB Hub, 4 port 2.0 for SDM-03
82-6051RK	USB Hub, 7 port 2.0 for SDM-03
71-8007RK	SDM-03 Product CD

SPECIFICATIONS

Input Power	12 VDC NOTE: AC Adapter with 100 - 240 VAC, 50/60 Hz, 0.6A input and 12 VDC, 1.2A output provided as standard.
Environmental Conditions	<ul style="list-style-type: none"> For Indoor Use Only -10° C to 40° C, below 80% Relative Humidity, Non-Condensing
Applicable Instruments	03 Series
Maximum Number of Records Saved	200 (stand-alone). Unlimited with software
3 Ports	1 Calibration gas, 1 fresh air and 1 exhaust
Standard Accessories	<ul style="list-style-type: none"> AC Adapter USB Flash Drive Single Module Data Viewer Software SDM-03 Docking Station PC Controller Program Inlet Air Filter Instruction Manual 10 Foot Long Exhaust Tube One 3 Foot Long Tube for GAS Fitting 2 T-Fittings (for PC Controlled Configuration only) 10 Foot Long 3/16 Inch Tube for GAS manifolding (used for PC Controlled Configuration only) Check Valve (used for PC Controlled Configuration only) USB Cable, Type A to Type B



Control Panel View



SDM Back View