



# HYDROGEN SULPHIDE TRANSMITTER & SENSOR

## LEADERS IN GAS DETECTION

Since 1977

## H<sub>2</sub>S SENSOR (R65-2424RK)



### Features:

- Water/dust resistant housing
- Sensor and Amplifier
- Long life sensors (2+ years typical)
- Competitively priced
- Compact design

### Applications:

- Water & wastewater treatment plants
- Pulp & paper mills
- Gas, telephone & electric utilities
- Parking garages
- Manufacturing facilities
- Loading Docks

This Hydrogen Sulphide transmitter is a highly reliable and very cost effective 4-20 mA transmitter for the detection of Hydrogen Sulphide gases. The electronics are protected inside the polycarb enclosure to avoid damage from mechanical abuse, water, dust or corrosion. Sensors for H<sub>2</sub>S are long life and typically last 2 - 3 years.

The transmitter operates from 24 VDC (18VDC to 30 VDC), and provides a 4-20 mA signal which. This allows the sensor to be connected directly to the Beacon Controller series. The Hydrogen Sulphide transmitter can be used either indoors or in outdoor areas.

The only tools required to calibrate the low cost H<sub>2</sub>S transmitter are a multimeter, screwdriver, and calibration gas. The zero and calibration functions are performed by adjusting the amplifier board. The amplifier board has test jacks for the connection of a ammeter for calibration purposes. The sensor response is viewed on the multimeter as a milliamp signal. Field calibration can be performed easily and quickly by one person.

### Specifications:

<b>Sensor Type</b>	Electrochemical	<b>Temperature range</b>	-10°C to 50°C
<b>Measuring range</b>	0 - 100 ppm	<b>Humidity range</b>	0% to 95% non-condensing
<b>Resolution</b>	1ppm	<b>Connections</b>	2 Core, shielded, 1.5 mm
<b>Linearity</b>	± 5% F.S.	<b>Operating Voltage</b>	18 to 30 VDC
<b>Response time</b>	Less than 60 sec to 90% of gas applied	<b>Output</b>	4 – 20mA
<b>Life Expectancy</b>	3 to 5 Years normal service	<b>Maximum Current Draw</b>	24mA (2-wire system)
<b>Dimensions</b>	150mm (L) x 64mm (H) x 82mm (W)	<b>Enclosure</b>	IP66, Polycarb

**Head Office:**  
Unit 1 / 3 Deakin Street  
(PO Box 5904)  
Brendale QLD 4500 Australia  
Ph: +61 (0) 7 3481 9000

**Perth Office:**  
Unit 5 / 30 Enterprise Crescent  
Malaga WA 6090 Australia  
Ph: +61 (0) 8 6184 7840  
[sales@controlequipment.com.au](mailto:sales@controlequipment.com.au)

**Representatives/Offices in:**  
Sydney Melbourne  
Hobart Adelaide  
Auckland Wellington  
[www.controlequipment.com.au](http://www.controlequipment.com.au)