

OI-9100

Wireless Gas Monitor

- Hand held
- Shows status of any GEN II sensor
- Ideal for commissioning or portable viewing
- Ability to read gas and battery levels



OVERVIEW

The Wireless View OI-9100 is a hand held signal strength meter specifically engineered to show the status of any Wireless Gen II gas detection device within range.

The View features a 4-line scrollable display. Using a 4 column read, the View is capable of revealing the Channel, Reading, Signal Strength and Time Since Last Message of any Wireless device on site as well as the Sensor, Gas and Battery. The View contains a 900Mhz,100mW, 10km Line Of Site (LOS) radio ensuring prompt and accurate communication with other Gen II Wireless devices.

The ability of the View to continuously notify the user of each Wireless devices status at a particular site make the device a truly phenomenal safety product to be introduced into the industry.

APPLICATIONS

- Blast Mining
- Petrochemical plants
- Refineries
- Water & wastewater treatment plants
- Gas, telephone & electric utilities
- Parking garages
- Manufacturing facilities
- HVAC
- Laboratories

Operating Power	Two 3.7V Rechargeable Lithium Ion Batteries
Power	+12-35 Volts DC
Battery Life	16 hours (continuous use)
Radio Options	900MHz ISM, 200mW, 11 km LOS (line of site)
Protection	PTC Resetting Fuses (automatic resettable)
Display	4 x 20 character alpha numeric LCD
Enclosure	Black Aluminium, powder coated
Enclosure Size	123 x 102 x 30mm
Warranty	Hardware 1 year (limited)